

Premier Elite 32XP-W (GCA0015)



Features Premier Elite 32XP-W

- Operating Frequency 866.0-866.6 Mhz
- Ricochet wireless mesh technology wireless receiver
- Add to any Premier/Premier Elite panel for wireless expansion
- Up to 32 Wireless Sensors (Panel Dependent)
- Tamper Protected
- Ricochet Monitor Software Connectivity through USB-Com
- Suitable for commercial and residential indoor applications
- EN50131-1, EN50131-5-3, EN50131-3, PD6662, Grade 2 Class II

Refer to Installation Manual for compatibility and sensor configuration with different panels

Technical Specifications

Frequency	866.0-866.6 Mhz
Operating Voltage	10-13.7 VDC
Current Consumption	<120mA
Network	4 wire standard 7/0.2 alarm cable up to 250m. Star/Daisy Chain or any combination
Operating temp	-10°C to +50°C (14°F to 131°F)
Dimensions	170mm x 140mm x 35mm (HxWxD)
Relative humidity	Max. 95%
Weight	500g



Certificate Number: FM 35285

Texecom

www.texe.com

Texecom Limited, Bradwood Court, St. Crispin Way, Haslingden, Lancashire BB4 4PW,
England.

Technical Support:

UK Customers Tel: 08456 300 600

(Calls charged at 3.36 pence per minute from a BT landline. Calls from other networks may vary.)

International Customers Tel: +44 1278 411707

Email: techsupport@texe.com