

Texecom

Designed to Perform

Texecom Limited

Bradwood Court, St. Crispin Way,
Haslingden, Great Britain BB4 4PW

Telephone (General) +44 (0)1706 234800

Facsimile (Sales) +44 (0)1706 223450

Email intsales@texe.com

Premier Elite Odyssey 3 (FCC2573)



Features:

Environmentally sealed microprocessor technology, twin piezo sounders and triple tamper protection ensure uncompromising performance. Competitively priced and easy to install, this is the clear choice for all professional installations.

The advanced electronic module of the Premier Elite Odyssey 3 is protected by a robust inner cover assembly with gasket seal. This maximises protection from dust and moisture, sealing to IP65 rating which enables prolonged exposure to harsher environments without compromising performance or functionality.

Texecom's new Premier Elite Odyssey external sounders combine high output audible and visual alarm signalling, conforming to PD6662:2010 Grade 3 Class IV.

- ✓ Twin Piezo Sounders Producing 115dB(A)
- ✓ IP65 Sealed Electronics Module
- ✓ Wall, Lid & Screw Tamper Detection
- ✓ Patented Engineer Hold-Off Mode
- ✓ Range of Colours Available



Certificate Number: FM 35285

Registered Office: Bradwood Court, St. Crispin Way, Haslingden, Lancs BB4 4PW.
Registered in England No. 2084170

- ✓ Battery Monitoring with Fault Output
- ✓ PD6662:2010 Grade 3 Class IV
- ✓ EN50131-1, EN50131-4 Grade 3 Class IV

Technical Specifications:

Electrical	
Supply Voltage:	12-16 VDC (13.7 nominal)
Current Drain (typical at 13.7VDC):	Strobe: 100mA
	Ody 3 : 405mA 190mA 30mA
	Quiescent: 18mA
Standby Battery	Type: NiMh Stack
	Voltage: 7.2VDC (nominal)
	Capacity: 250mAh
Flash Tube:	1Ws Xenon
Flash Rate:	1Hz (typical)*
Discharge Time (<60VDC):	<180 seconds
Comfort LEDs Brightness:	100mcd (typical)
Flash Rate (tamper secure):	1Hz alternating (typical)

Environmental	
Volume (SAB mode at 13.7VDC)	Ody 3 : 115dB Peak at 1m (A Weighting, 90°)
Cut-Off Time:	<15 minutes
Environmental Protection:	Ody 3 : IP65
Operating Temperature:	-25°C (-13°F) to +55°C (+131°F)
Storage Temperature:	-25°C (-13°F) to +60°C (+140°F)
EMC Environment:	Residential / Commercial / Industrial

Physical	
Material	3mm Ploycarbonate
Tamper Detection	Ody 3 : Wall, screw & lid
Dimensions (h x w x d)	315mm x 306mm x 78mm
Packed Weight	Ody 3 : 1250g approx

